

FLOTATION 648 - Технические спецификации



Description

Шины FLOTATION 648 особенно подходят для техники, используемой для перевозок по полям и дорогам, а также для разбрасывателей. Некоторые размерности разработаны для сенокосилок/сеновязалок. Особый рисунок протектора позволяет перевозить большие грузы, оказывая низкое давление на поверхность земли, что снижает уплотнение почвы и предотвращает повреждение культур.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка •
Разбрасыватель

Version	HD
Type	TL
Tyre Size	650/65 - 30.5
LI/SS DRIVE WHEEL	167 A8/163 B
LI/SS FREE ROLLING	179 A8/175 B

Dimensions US Standard

Usa code	94030149
Ply Rating	16
Section Width (inch)	26.4
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 20.00
ECE	E11-106R-004562

Load capacity (lbs)

mph / psi	26	29	32
5 FR	21260	22620	23920
10 FR	19140	20360	21530
20 FR	17010	18100	19140
25 FR	15190	16160	17080
30 FR	13670	14540	15210
5 DW	14960	15910	16820
10 DW	13460	14320	15130
20 DW	11960	12730	13460
25 DW	10680	11360	12010
30 DW	9610	10230	10750

Printed on 19.04.2024 15:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..