

FLOTATION 648 - Технические спецификации



Description

Шины FLOTATION 648 особенно подходят для техники, используемой для перевозок по полям и дорогам, а также для разбрасывателей. Некоторые размерности разработаны для сенокосилок/сеновязалок. Особый рисунок протектора позволяет перевозить большие грузы, оказывая низкое давление на поверхность земли, что снижает уплотнение почвы и предотвращает повреждение культур.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка •
Разбрасыватель

Version	STANDARD
Type	TL
Tyre Size	700/50 - 26.5
LI/SS DRIVE WHEEL	157 A8/154 B
LI/SS FREE ROLLING	169 A8/165 B

Dimensions US Standard

Usa code	94006519
Ply Rating	12
Section Width (inch)	27.6
Overall Diameter (inch)	54.1
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	161.4
Rim Rec	24.00
ECE	E4-106R-002278

Load capacity (lbs)

mph / psi	22	23	26
5 FR	16090	16710	17900
10 FR	14480	15050	16110
20 FR	12870	13370	14320
25 FR	11500	11940	12790
30 FR	10350	10750	11350
5 DW	11450	11880	12730
10 DW	10310	10690	11460
20 DW	9160	9500	10180
25 DW	8180	8490	9090
30 DW	7360	7640	8270

Printed on 19.04.2024 20:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..