

FLOTATION TR 675 - Загрузить лист технических данных



Description

Шины FLOTATION TR 675 лучше всего подходят для машин, которые используются для перевозок в поле и по дорогам. Они устанавливаются на прицепы и сельскохозяйственную технику. Шины FLOTATION TR 675 разрабатывались для обеспечения выдающейся тяги, высокой грузоподъемности и увеличенного срока службы.

UM

International Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Прицеп

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/60 - 22.5	DUAL BEAD	155 A8/151 B	168 A8/164 B	20	AG 16.00	15.00 ; 17.00	515	1181	542	3604	TL	E11-106R-004395
500/60 - 22.5	STANDARD	145 A8/142 B	157 A8/154 B	12	AG 16.00	15.00 ; 17.00	515	1181	542	3604	TL	E4-106R-002314
500/60 - 22.5	STANDARD	151 A8/ 148 B	163 A8/159 B	16	AG 16.00	15.00 ; 17.00	515	1181	542	3604	TL	E11-106R-003605
550/45 - 22.5	STANDARD	154 A8/150 B	166 A8/162 B	20	AG 16.00		543	1070	0	0	TL	E4-106R-002723
550/60 - 22.5	STANDARD	148 A8/144 B	160 A8/156 B	12	AG 16.00		550	1260	547	3640	TL	E11-106R-004396
550/60 - 22.5	STANDARD	154 A8/150 B	167 A8/163 B	16	AG 16.00		550	1260	547	3640	TL	E11-106R-004397

Printed on 26.04.2024 8:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..