

## FLOTATION TR 678 - Технические спецификации



### Description

Шины FLOTATION TR 678 специально разработаны для прицепов и сельскохозяйственного прицепного оборудования, эксплуатируемого как на дороге, так и на бездорожье. Они могут выдерживать очень большую нагрузку при низком давлении воздуха, снижая уплотнение почвы. Эта модель демонстрирует отличные тяговые характеристики и способность к самоочищению.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •  
Прицеп

|                    |               |
|--------------------|---------------|
| Version            | DUAL BEAD HD  |
| Type               | TL            |
| Tyre Size          | 600/40 - 22.5 |
| LI/SS DRIVE WHEEL  | 157 A8        |
| LI/SS FREE ROLLING | 169 A8        |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 20              |
| Section Width (mm)         | 615             |
| Overall Diameter (mm)      | 1085            |
| Static Loaded Radius (mm)  | 483             |
| Rolling Circumference (mm) | 3264            |
| Rim Rec                    | AG 20.00        |
| ECE                        | E11-106R-004619 |

## Load capacity (Kg)

| km/h / bar | 6.00 |
|------------|------|
| 40         | 5800 |

Printed on 26.02.2024 21:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..