

FLOTATION TR 678 - Технические спецификации



Description

Шины FLOTATION TR 678 специально разработаны для прицепов и сельскохозяйственного прицепного оборудования, эксплуатируемого как на дороге, так и на бездорожье. Они могут выдерживать очень большую нагрузку при низком давлении воздуха, снижая уплотнение почвы. Эта модель демонстрирует отличные тяговые характеристики и способность к самоочищению.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Прицеп

Version	STEEL BELTED
Type	TL
Tyre Size	650/45 - 22.5
LI/SS	166 B

Dimensions US Standard

Usa code	94030170
Ply Rating	20
Section Width (inch)	25.6
Overall Diameter (inch)	45.3
Static Loaded Radius (inch)	19.8
Rolling Circumference (inch)	130
Rim Rec	AG 20.00
ECE	E11-106R-004401

Load capacity (lbs)

mph / psi	65
30	11680

Printed on 23.02.2024 15:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..