

## FLOTATION V LINE - Технические спецификации



### Description

Шины FLOTATION V LINE разработаны специально для эксплуатации на прицепах, используемых для грузовых перевозок. Они демонстрируют высокую проходимость и обеспечивают низкий уровень уплотнения почвы, защищая поле. Шины FLOTATION V LINE позволяют перевозить большие грузы при низком давлении на поверхность земли, максимально повышая производительность вашей работы.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Прицеп

|                    |               |
|--------------------|---------------|
| Version            | STANDARD      |
| Type               | TL            |
| Tyre Size          | 550/60 - 22.5 |
| LI/SS DRIVE WHEEL  | 154 A8/150 B  |
| LI/SS FREE ROLLING | 167 A8/163 B  |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94006236       |
| Ply Rating                   | 16             |
| Section Width (inch)         | 21.7           |
| Overall Diameter (inch)      | 48.8           |
| Static Loaded Radius (inch)  | 21.3           |
| Rolling Circumference (inch) | 146.7          |
| Rim Rec                      | AG 16.00       |
| ECE                          | E4-106R-001563 |

## Load capacity (lbs)

| mph / psi | 35    | 38    | 41    |
|-----------|-------|-------|-------|
| 5 FR      | 15370 | 16110 | 16820 |
| 10 FR     | 13830 | 14490 | 15130 |
| 20 FR     | 12300 | 12890 | 13460 |
| 25 FR     | 10980 | 11510 | 12010 |
| 30 FR     | 9880  | 10360 | 10750 |
| 5 DW      | 10570 | 11080 | 11570 |
| 10 DW     | 9510  | 9980  | 10420 |
| 20 DW     | 8450  | 8860  | 9260  |
| 25 DW     | 7550  | 7910  | 8270  |
| 30 DW     | 6800  | 7120  | 7390  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.05.2025 18:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..