

## FORESTECH - Технические спецификации



### Description

FORESTECH — это диагональные шины компании BKT с брекером из металлокорда для форвардеров, используемых в лесном хозяйстве. Они обеспечивают великолепную тягу даже при больших нагрузках. Прочный борт и плечевая зона этих шин гарантируют высокое сопротивление проколам, что значительно продлевает срок службы шины. В результате вы сможете успешно покорить даже самые непроходимые леса.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Погрузочно-транспортная машина

|           |               |
|-----------|---------------|
| Version   | STEEL BELTED  |
| Type      | TL            |
| Tyre Size | 710/45 - 26.5 |
| LI/SS     | 168 A8/175 A2 |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 20              |
| Section Width (mm)         | 710             |
| Overall Diameter (mm)      | 1340            |
| Static Loaded Radius (mm)  | 620             |
| Rolling Circumference (mm) | 4047            |
| Rim Rec                    | AG 24.00        |
| ECE                        | E11-106R-003420 |
| TRA Code                   | LS2             |

## Load capacity (Kg)

| km/h / bar | 5.00 |
|------------|------|
| 40         | 5600 |
| 30         | 5990 |
| 10         | 6900 |

Printed on 28.04.2024 2:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..