

GIANT TRAX - Технические спецификации



Description

Шины GIANT TRAX разработаны для погрузчиков с бортовым поворотом, которые работают на неровных поверхностях, какие обычно бывают на складах металлолома и в пунктах переработки, а также в условиях горных разработок. Очень глубокий рисунок протектора с более широкими и жесткими блоками гарантирует лучшие тяговые характеристики, устойчивость и сопротивление проколам. Специальная резиновая смесь протектора обеспечивает исключительную устойчивость к порезам и разрывам наряду с отличной износостойкостью при эксплуатации на любом типе поверхности.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	STANDARD
Type	TL
Tyre Size	14 - 17.5

Dimensions US Standard

Usa code	94064403
Ply Rating	14
Section Width (inch)	13.8
Overall Diameter (inch)	36
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	106.9
Rim Rec	10.50
ECE	E11-106R-006019

Load capacity (lbs)

mph / psi	80
5	8540
10	6750
15	6240

Printed on 24.04.2024 12:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..