

## GRIP STAR - Технические спецификации



### Description

GRIP STAR - это агропромышленные шины для телескопических погрузчиков, выполняющих погрузочные работы. Они демонстрируют отличные тяговые характеристики и самоочистительную способность. Кроме того, это всесезонные шины, подходящие для эксплуатации на илистых почвах. Шины GRIP STAR также доступны в версии «Special», которая отличается более высокой устойчивостью к порезам и разрывам.

### UM

US Standard

### Construction

 BIAS

### Machinery

Производство: Телескопический погрузчик

Version	SPECIAL
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	151 A6
LI/SS FREE ROLLING	163 A6

## Dimensions US Standard

Usa code	94035977
Ply Rating	16
Section Width (inch)	15.4
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	145
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L

## Load capacity (lbs)

mph / psi	58
20 FR LLV	10750
20 DW LLV	7610

Printed on 27.04.2024 4:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..