

HARVESTER SPECIAL - Технические спецификации



Description

Шина HARVESTER SPECIAL была специально разработана для уборочной техники. Двойной угол наклона блоков протектора гарантирует как отличные тяговые характеристики при движении по полю, так и комфорт при езде по дороге. Специальный рисунок протектора обеспечивает большое пятно контакта для выдающейся устойчивости. Шина HARVESTER SPECIAL с прочным каркасом и особенно устойчивой к порезам и проколам резиновой смесью гарантирует долгий срок службы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Комбайн

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	159 A6

Dimensions International Standard

Ply Rating	16
Section Width (mm)	587
Overall Diameter (mm)	1585
Static Loaded Radius (mm)	720
Rolling Circumference (mm)	4806
Rim Rec	DW 20 B ; DW 20 A
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.30
30	4375

Printed on 25.04.2024 16:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..