

HARVESTER SPECIAL - Технические спецификации



Description

Шина HARVESTER SPECIAL была специально разработана для уборочной техники. Двойной угол наклона блоков протектора гарантирует как отличные тяговые характеристики при движении по полю, так и комфорт при езде по дороге. Специальный рисунок протектора обеспечивает большое пятно контакта для выдающейся устойчивости. Шина HARVESTER SPECIAL с прочным каркасом и особенно устойчивой к порезам и проколам резиновой смесью гарантирует долгий срок службы.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Комбайн

Version	DUAL BEAD
Type	TL
Tyre Size	23.5 - 25

Dimensions US Standard

Usa code	94065882
Ply Rating	20
Section Width (inch)	24.2
Overall Diameter (inch)	65.6
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	199.1
Rim Rec	19.50/2.5
ECE	E11-106R-006954
TRA Code	R1

Load capacity (lbs)

mph / psi	54
5	24000

Printed on 25.04.2024 16:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..