

I - 1 - Технические спецификации



Description

Шины I-1 разработаны для машин, используемых для грузовых перевозок по полю и дороге, а также для сельскохозяйственной техники и прицепов, которые задействованы в процессе обработки почвы. I-1 — это скоростные шины, которые оптимизируют временные затраты, позволяя вам сконцентрироваться на основной деятельности. Особая конструкция шины обеспечивает ей долговечность даже в суровых условиях, а также устойчивость к воздействию пожнивных остатков.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Прицеп

Version	STANDARD
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS FREE ROLLING	118 D

Dimensions International Standard

Ply Rating	12
Section Width (mm)	270
Overall Diameter (mm)	765
Rim Rec	9.00
ECE	E11-106R-006267

Load capacity (Kg)

km/h / bar	4.70
65	1320

Printed on 06.12.2023 6:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..