I - 1 - Технические спецификации

Description

Шины I-1 разработаны для машин, используемых для грузовых перевозок по полю и дороге, а также для сельскохозяйственной техники и прицепов, которые задействованы в процессе обработки почвы. I-1 — это скоростные шины, которые оптимизируют временные затраты, позволяя вам сконцентрироваться на основной деятельности. Особая конструкция шины обеспечивает ей долговечность даже в суровых условиях, а также устойчивость к воздействию пожнивных остатков.

UM

US Standard

Construction

BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование • Прицеп

Version	STANDARD
Type	TT
Tyre Size	10.5/80 - 18
LI/SS FREE ROLLING	135 A8

Dimensions US Standard

Usa code	94057146
Ply Rating	12
TMPH	1
Section Width (inch)	11
Overall Diameter (inch)	35
Static Loaded Radius (inch)	16.4
Rolling Circumference (inch)	105.5
Rim Rec	W 9
Rim Alt	W 8 ; 9
TRA Code	I1

Load capacity (lbs)

mph / psi	64
5 FR	6720
15 FR	5720
20 FR	5380
25 FR	4810

Printed on 28.04.2024 22:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..