

## IT 400 - Технические спецификации



### Description

IT 400 - это шины с продольными ребрами для прицепов с низкой платформой, используемых для дорожных грузовых перевозок. Эти шины подходят для техники, от которой требуется высокая скорость, и гарантируют значительную экономию топлива.

### UM

International Standard

### Construction

 BIAS

### Machinery

Производство: Прицеп с низкой платформой

Version	STANDARD
Type	TL
Tyre Size	8.25 - 15
LI/SS	129/125 J

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	239
<b>Overall Diameter (mm)</b>	846
<b>Static Loaded Radius (mm)</b>	377
<b>Rolling Circumference (mm)</b>	2513
<b>Rim Rec</b>	6.50
<b>Rim Alt</b>	6.0 ; 7.0
<b>ECE</b>	E11-54R-0018586

## Load capacity (Kg)

km/h / bar	8.60	7.90	7.20
15	2960	-	-
30	-	2440	-
100 LS	-	1850	-
100 LD	-	-	1650

Printed on 23.04.2024 13:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..