

JUMBO TRAX HD - Технические спецификации



Description

JUMBO TRAX HD - это шины с блочным рисунком протектора для погрузчиков с бортовым поворотом. Они отличаются высокой устойчивостью к порезам и разрывам и особенно подходят для эксплуатации при больших нагрузках. Глубокий рисунок протектора наряду с превосходной защитой боковин обеспечивают более продолжительный срок службы шины. Шины JUMBO TRAX HD также доступны в версии «Special».

UM

International Standard

Construction

 BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	120 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	268
Overall Diameter (mm)	795
Static Loaded Radius (mm)	363
Rolling Circumference (mm)	2345
Rim Rec	8.25
ECE	E11-106R-003523

Load capacity (Kg)

km/h / bar	5.20
40	1400

Printed on 27.04.2024 6:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..