LG 306 - Технические спецификации

Description

LG 306 — это шины для садово-огородной техники, включая газонокосилки. Некоторые размерности также подходят для компактных тракторов. За счет особого рисунка протектора шины практически не уплотняют почву и одновременно обеспечивают превосходную управляемость. Шины LG 306 также предлагаются с брекером из арамидного волокна в версии «Aramid-belted» с более высоким сопротивлением проколам.

UM

International Standard

Construction

BIAS

Machinery

Сельское хозяйство: Газонокосилка • Мини-трактор

Version	STANDARD
Type	TL
Tyre Size	26 X 12.00 - 12

Dimensions International Standard

Ply Rating	8
Section Width (mm)	310
Overall Diameter (mm)	640
Static Loaded Radius (mm)	283
Rolling Circumference (mm)	1856
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90
Rim Alt	10½ JA ; 8½ JA
ECE	E4-106R-002674

Load capacity (Kg)

km/h / bar	3.00
15	1250

Printed on 26.04.2024 12:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..