

LG 306 - Технические спецификации



Description

LG 306 — это шины для садово-огородной техники, включая газонокосилки. Некоторые размерности также подходят для компактных тракторов. За счет особого рисунка протектора шины практически не уплотняют почву и одновременно обеспечивают превосходную управляемость. Шины LG 306 также предлагаются с брекером из арамидного волокна в версии «Aramid-belted» с более высоким сопротивлением проколам.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Газонокосилка • Мини-трактор

Version	ARAMID BELTED
Type	TL
Tyre Size	31 X 15.5 - 15

Dimensions US Standard

Usa code	94062775
Ply Rating	8
Section Width (inch)	15.4
Overall Diameter (inch)	31.2
Static Loaded Radius (inch)	13.8
Rolling Circumference (inch)	91.1
Rim Rec	13 LB
ECE	E11-106R-006735

Load capacity (lbs)

mph / psi	45
30	2760

Printed on 28.04.2024 22:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..