

## LG 307 - Технические спецификации



### Description

LG 307 — это шины для садово-огородной техники, включая газонокосилки. За счет особого рисунка протектора шины практически не уплотняют почву, защищая ее поверхностный слой, и одновременно обеспечивают превосходную управляемость.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Газонокосилка

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 8

## Dimensions US Standard

Usa code	94012831
Ply Rating	4
Section Width (inch)	10
Overall Diameter (inch)	19.5
Static Loaded Radius (inch)	8.5
Rolling Circumference (inch)	56.5
Rim Rec	8.00 I - 55 ; I - 70 ; I - 90
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005200

## Load capacity (lbs)

mph / psi	22
10	1200

Printed on 23.04.2024 20:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..