

LG 408 - Технические спецификации



Description

LG 408 — это шины для садово-огородной техники, включая газонокосилки и компактные тракторы. За счет особого рисунка протектора шины практически не уплотняют почву, защищая ее поверхностный слой, и одновременно обеспечивают превосходную управляемость. Шины LG 408 также предлагаются с брекером из арамидного волокна в версии «Aramid-belted» с более высоким сопротивлением проколам.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Газонокосилка • Мини-трактор

| | |
|-----------|-------------------|
| Version | ARAMID BELTED |
| Type | TL |
| Tyre Size | 26.5 X 14.00 - 12 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94012916 |
| Ply Rating | 6 |
| Section Width (inch) | 15 |
| Overall Diameter (inch) | 26.2 |
| Static Loaded Radius (inch) | 11.5 |
| Rolling Circumference (inch) | 75.9 |
| Rim Rec | 12.00 I |
| ECE | E11-106R-005223 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 30 |
| 10 | 2820 |

Printed on 26.04.2024 21:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..