

LG RIB PLUS - Технические спецификации



Description

Шины LG RIB PLUS предназначены для садово-огородной техники, включая газонокосилки, компактные тракторы и сеноворошилки.

Специальный рисунок протектора способствует щадящему контакту с землей, помогает избежать повреждения дерна и при этом обеспечивает повышенную управляемость.

Благодаря своему круглому профилю шина LG RIB PLUS демонстрирует отличные характеристики скольжения и сцепления при выполнении поворотов во время полевых работ.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Газонокосилка • Мини-трактор

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions US Standard

Usa code	94065530
Ply Rating	10
Section Width (inch)	6.7
Overall Diameter (inch)	16.1
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90

Load capacity (lbs)

mph / psi	72
10	1060

Printed on 19.04.2024 23:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..