

LG RIB PLUS - Загрузить лист технических данных



Description

Шины LG RIB PLUS предназначены для садово-огородной техники, включая газонокосилки, компактные тракторы и сеноворошилки.

Специальный рисунок протектора способствует щадящему контакту с землей, помогает избежать повреждения дерна и при этом обеспечивает повышенную управляемость.

Благодаря своему круглому профилю шина LG RIB PLUS демонстрирует отличные характеристики скольжения и сцепления при выполнении поворотов во время полевых работ.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Газонокосилка • Мини-трактор

| SIZE | Version | PR | RIM REC | RIM ALT | SW | OD | Type |
|---------------|----------|----|--------------------------------|---------|-----|-----|------|
| 16 X 6.50 - 8 | STANDARD | 10 | 5.375 I - 55 ; I - 70 ; I - 90 | | 170 | 408 | TL |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08.12.2024 5:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..