

LOADER PLUS - Технические спецификации



Description

LOADER PLUS (L-3) - это диагональные шины, разработанные специально для погрузчиков. Резиновая смесь протектора гарантирует высокую устойчивость к порезам и разрывам, за счет чего шины идеально подходят для эксплуатации на погрузчиках и бульдозерах.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Бульдозер • Погрузчик

Производство: Бульдозер • Погрузчик

Version	STANDARD
Type	TT
Tyre Size	17.5 - 25

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	440
Overall Diameter (mm)	1345
Static Loaded Radius (mm)	622
Rolling Circumference (mm)	3980
Rim Rec	14.00/1.5
TRA Code	L3
Tread Depth	26

Load capacity (Kg)

km/h / bar	4.75
10	7300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25.03.2025 7:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..