

## LOADER PLUS - Технические спецификации



### Description

LOADER PLUS (L-3) - это диагональные шины, разработанные специально для погрузчиков. Резиновая смесь протектора гарантирует высокую устойчивость к порезам и разрывам, за счет чего шины идеально подходят для эксплуатации на погрузчиках и бульдозерах.

### UM

US Standard

### Construction

 BIAS

### Machinery

Производство: Бульдозер • Погрузчик

Производство: Бульдозер • Погрузчик

Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

## Dimensions US Standard

Usa code	94065011
Ply Rating	16
Overall Width (inch)	24
Overall Diameter (inch)	64.6
Static Loaded Radius (inch)	29.5
Rolling Circumference (inch)	191.1
Rim Rec	19.50/2.5
TRA Code	L3
Tread Depth	41

## Load capacity (lbs)

mph / psi	44
5	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.03.2025 11:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..