

## LOADER SPECIAL - Технические спецификации



### Description

LOADER SPECIAL (L-5) - это диагональные шины, которые станут надежным спутником ваших погрузчиков, помогая повысить эффективность горных работ даже при огромных нагрузках. Оптимальные тяговые характеристики и исключительное сопротивление порезам помогут значительно увеличить производительность.

### UM

US Standard

### Construction

 BIAS

### Machinery

Производство: Бульдозер • Погрузчик

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TL        |
| Tyre Size | 26.5 - 25 |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94034536  |
| Ply Rating                   | 28        |
| Overall Width (inch)         | 27        |
| Overall Diameter (inch)      | 71.5      |
| Static Loaded Radius (inch)  | 32.8      |
| Rolling Circumference (inch) | 211.5     |
| Rim Rec                      | 22.00/3.0 |
| TRA Code                     | L5        |

## Load capacity (lbs)

|           |       |
|-----------|-------|
| mph / psi | 69    |
| 5         | 34200 |

Printed on 28.04.2024 22:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..