

LOADER SPECIAL - Загрузить лист технических данных



Description

LOADER SPECIAL (L-5) - это диагональные шины, которые станут надежным спутником ваших погрузчиков, помогая повысить эффективность горных работ даже при огромных нагрузках. Оптимальные тяговые характеристики и исключительное сопротивление порезам помогут значительно увеличить производительность.

UM

International Standard

Construction

❖ BIAS

Machinery

Производство: Бульдозер • Погрузчик

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
20.5 - 25	STANDARD	L5	20	17.00/2.0		530	1570			TL	85
26.5 - 25	STANDARD	L5	32	22.00/3.0		686	1815	833	5372	TL	94
26.5 - 25	STANDARD	L5	28	22.00/3.0		686	1815	833	5372	TL	94
29.5 - 25	STANDARD	L5	32	25.00/3.5		770	1930	884	5753	TL	100
29.5 - 25	STANDARD	L5	28	25.00/3.5		770	1930	884	5753	TL	100
35/65 - 33	STANDARD	L5	42	28.00/3.5		910	2105	976	6505	TL	100
40/65 - 39	STEEL BELTED	L5	56	32.00/4.0		1000	2405	0	0	TL	108
45/65 - 45	STEEL BELTED	L5	58	36.00/4.5		1185	2785	0	0	TL	116

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23.04.2025 13:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..