

LP 450 - Технические спецификации



Description

LP 450 - это шины для прицепов с низкой платформой, используемых для дорожных грузовых перевозок. Эти скоростные шины обеспечивают значительную экономию топлива, а также отличаются долгим сроком службы.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Прицеп с низкой платформой

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

Dimensions International Standard

Ply Rating	12
Section Width (mm)	214
Overall Diameter (mm)	710
Static Loaded Radius (mm)	321
Rolling Circumference (mm)	2109
Rim Rec	6.00 MH

Load capacity (Kg)

	km/h / bar	6.90
	100 LS	1285
	100 LD	1130

Printed on 17.04.2024 19:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..