

LUG STAR - Технические спецификации



Description

LUG STAR — это промышленная шина, разработанная для дорожных и железнодорожных экскаваторов, которым требуется превосходная тяга. Шина отличается исключительными свойствами самоочистки и стойкостью резиновой смеси. Прочный каркас обеспечивает превосходную долговечность.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Автомобильно-железнодорожное транспортное средство

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 10.00 - 20 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Ply Rating | 18 |
| Overall Width (mm) | 280 |
| Overall Diameter (mm) | 1080 |
| Static Loaded Radius (mm) | 506 |
| Rolling Circumference (mm) | 3343 |
| Rim Rec | 7.5 |
| Rim Alt | 7.0 ; 8.0 |

Load capacity (Kg)

| km/h / bar | 10.00 |
|------------|-------|
| 10 | 6890 |
| 25 | 5300 |

Printed on 27.04.2024 3:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..