MAGLIFT EXCAVATOR - Технические спецификации

Description

ШИНА MAGLIFT EXCAVATOR специально разработана для колесных экскаваторов, используемых в землеройных, погрузочно-разгрузочных и дорожных работах. Шина изготавливается с применением особой резиновой смеси протектора, которая гарантирует превосходные показатели устойчивости к порезам и разрывам, а также длительный срок службы. Агрессивный рисунок протектора обеспечивает высокий уровень комфорта с точки зрения управляемости, а также превосходное поперечное сцепление даже при большой нагрузке, не говоря об отличных характеристиках самоочистки. Усиленная конструкция борта позволяет достичь лучшего сцепления с покрытием и предотвращает риск проскальзывания колес в процессе работы, а его особая форма облегчает установку на колесный диск. MAGLIFT EXCAVATOR — это защищенная от проколов и не требующая обслуживания шина, на которую операторы техники могут положиться.

UM

International Standard

Construction

- SOLID

Machinery

Производство: Экскаватор

Version	STANDARD
Type	
Tyre Size	12.00 - 20

Dimensions International Standard

Overall Width (mm)	255
Overall Diameter (mm)	1100
Rim Rec	8.00 - 20

Load capacity (Kg)

km/h / bar	-
Static	9515
10	6865
25	6300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.05.2025 23:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..