

# MAGLIFT PREMIUM - Технические спецификации



## Description

MAGLIFT PREMIUM - это цельнолитая шина, специально разработанная для тяжелых вилочных погрузчиков, которые эксплуатируются в портах, на горнодобывающих предприятиях и складах металлолома. Сверхвысокий (на 25 выше, чем у стандартной версии шины), агрессивный и прочный рисунок протектора обеспечивает выдающееся продольное и поперечное сцепление, а также отличную управляемость. Благодаря уникальной резиновой смеси протектора эта шина демонстрирует отличную устойчивость к порезам и разрывам, что значительно продлевает срок ее службы. В число ее достоинств также входят низкое сопротивление качению и плавный ход.

## UM

US Standard

## Construction

◆ SOLID

## Machinery

Производство: Вилочный погрузчик

Version	LIP
Type	
Tyre Size	7.00 - 12

## Dimensions US Standard

Usa code	94055623
Section Width (inch)	6.4
Overall Diameter (inch)	26.1
Rim Rec	5.00 S - 12

## Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	6435
15 STEER WHEEL	4940

Printed on 26.04.2024 4:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..