

MP 567 - Технические спецификации



Description

MP 567 — агропромышленные шины, подходящие для перевозок по полю и по дороге, а также для муниципальных/ремонтных работ. Это идеальные шины для телескопических погрузчиков и сельскохозяйственной техники. Шины MP 567 гарантируют высокие тяговые характеристики в любых погодных условиях, а также отличаются превосходной способностью к самоочищению. Шины обеспечивают комфорт движения и увеличенный срок службы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Телескопический погрузчик
Производство: Телескопический погрузчик •
Универсальный автомобиль

Version	STANDARD
Type	TL
Tyre Size	10.5 - 20

Dimensions International Standard

Ply Rating	10
Section Width (mm)	270
Overall Diameter (mm)	955
Static Loaded Radius (mm)	445
Rolling Circumference (mm)	2880
Rim Rec	9
Rim Alt	9 SDC
ECE	E4-54R-0022630

Load capacity (Kg)

km/h / bar	3.75
90	1800
40	2070

Printed on 17.04.2024 17:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..