

## MP 567 - Технические спецификации



### Description

MP 567 — агропромышленные шины, подходящие для перевозок по полю и по дороге, а также для муниципальных/ремонтных работ. Это идеальные шины для телескопических погрузчиков и сельскохозяйственной техники. Шины MP 567 гарантируют высокие тяговые характеристики в любых погодных условиях, а также отличаются превосходной способностью к самоочищению. Шины обеспечивают комфорт движения и увеличенный срок службы.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •  
Телескопический погрузчик  
Производство: Телескопический погрузчик •  
Универсальный автомобиль

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	325
<b>Overall Diameter (mm)</b>	1040
<b>Static Loaded Radius (mm)</b>	490
<b>Rolling Circumference (mm)</b>	3142
<b>Rim Rec</b>	11.0
<b>Rim Alt</b>	12 SDC

## Load capacity (Kg)

	km/h / bar	4.50
	90	2300
	40	2750

Printed on 20.04.2024 22:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..