

MP 567 - Технические спецификации



Description

MP 567 — агропромышленные шины, подходящие для перевозок по полю и по дороге, а также для муниципальных/ремонтных работ. Это идеальные шины для телескопических погрузчиков и сельскохозяйственной техники. Шины MP 567 гарантируют высокие тяговые характеристики в любых погодных условиях, а также отличаются превосходной способностью к самоочищению. Шины обеспечивают комфорт движения и увеличенный срок службы.

UM

US Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Телескопический погрузчик
Производство: Телескопический погрузчик •
Универсальный автомобиль

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

Dimensions US Standard

Usa code	94038237
Ply Rating	12
Section Width (inch)	12.8
Overall Diameter (inch)	40.9
Static Loaded Radius (inch)	19.3
Rolling Circumference (inch)	123.7
Rim Rec	11.0
Rim Alt	12 SDC
ECE	E4-54R-0022633

Load capacity (lbs)

	mph / psi	51
	55	4410
	25	5070

Printed on 12.04.2024 16:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..