

## MP 570 - Технические спецификации



### Description

MP 570 — это агропромышленные шины для экскаваторов и экскаваторов-погрузчиков. Эти шины гарантируют отличные тяговые характеристики и долговечность техники, а также отличаются превосходной способностью к самоочищению в любых условиях эксплуатации.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Экскаватор-погрузчик  
Производство: экскаватор-погрузчик • Экскаватор •  
Универсальный автомобиль

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

## Dimensions International Standard

<b>Ply Rating</b>	10
<b>Section Width (mm)</b>	335
<b>Overall Diameter (mm)</b>	1050
<b>Static Loaded Radius (mm)</b>	480
<b>Rolling Circumference (mm)</b>	3130
<b>Rim Rec</b>	11
<b>Rim Alt</b>	12 SDC

## Load capacity (Kg)

	km/h / bar	3.00
	80	1850
	50	2065

Printed on 26.09.2023 18:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..