

## MP 585 - Технические спецификации



### Description

MP 585 — это агропромышленные дорожные шины для техники широкого профиля, используемой для муниципальных/ремонтных работ. Эти шины оснащены протектором со специальным рисунком, который обеспечивает их максимальную устойчивость и долговечность в самых сложных условиях эксплуатации.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Универсальный автомобиль  
Производство: Универсальный автомобиль

Version	STANDARD
Type	TL
Tyre Size	10.5 - 20

## Dimensions US Standard

Usa code	94038336
Ply Rating	10
Section Width (inch)	10.7
Overall Diameter (inch)	38.2
Static Loaded Radius (inch)	17.9
Rolling Circumference (inch)	113.8
Rim Rec	9
Rim Alt	9 SDC
ECE	E4-54R-0022631

## Load capacity (lbs)

	mph / psi	54
	55	3970
	30	4410

Printed on 09.05.2024 5:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..