

MP 600 - Технические спецификации



Description

MP 600 — это агропромышленные шины, которые обеспечивают комфорт движения. Они предназначены для телескопических погрузчиков и сельскохозяйственной техники, используемой при проведении муниципальных/ремонтных работ. Эти шины гарантируют отличную тягу, отличаются превосходной способностью к самоочищению и долгим сроком службы.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Телескопический погрузчик
Производство: Телескопический погрузчик •
Универсальный автомобиль

Version	STANDARD
Type	TL
Tyre Size	12.5 - 18

Dimensions US Standard

Usa code	94015306
Ply Rating	10
Section Width (inch)	12.1
Overall Diameter (inch)	39
Static Loaded Radius (inch)	17.7
Rolling Circumference (inch)	116.1
Rim Rec	11
Rim Alt	12 SDC

Load capacity (lbs)

mph / psi	44
25 DW	4540
30 DW	4410

Printed on 25.04.2024 20:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..