

MT 612 - Загрузить лист технических данных



Description

Шины MT 612 разработаны специально для техники широкого профиля, работающей как на дороге, так и на бездорожье. Их прочный каркас позволяет перевозить тяжелые грузы на высокой скорости, тогда как широкие грунтозацепы обеспечивают превосходные тяговые характеристики. Очень широкий рисунок протектора гарантирует отличную проходимость при движении по песчаным и илистым покрытиям.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Прицеп

Производство: Универсальный автомобиль

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.00 - 20	STANDARD	18	10		390	1265	594	3827	TT	
14.00 - 20	STANDARD	22	10		390	1265	594	3827	TT	
14.00 - 20	STANDARD	20	10		390	1265	594	3827	TT	E11-54R-0021125
16.0/70 - 20	STANDARD	16	13.00 T		405	1095	520	3327	TT	

Printed on 26.04.2024 17:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..