

MULTIMAX MP 522 - Технические спецификации



Description

MULTIMAX MP 522 — это универсальные шины компании BKT, разработанные для разнообразной агропромышленной техники. Они подходят для телескопических и компактных погрузчиков, а также другой техники, используемой для всех видов землеройных и погрузочных работ. Среди их преимуществ — устойчивость, тяга и исключительно высокое сопротивление проколам. Благодаря специальной резиновой смеси шины MULTIMAX MP 522 обладают невероятной устойчивостью к порезам и разрывам.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Компактный погрузчик •
Телескопический погрузчик
Производство: компактный погрузчик • Телескопический погрузчик

Version	STANDARD
Type	TL
Tyre Size	380/75 R 20 IND (14.5 R 20)
LI/SS	148 A8/B

Dimensions International Standard

Section Width (mm)	384
Overall Diameter (mm)	1074
Static Loaded Radius (mm)	483
Rolling Circumference (mm)	3251
SRI (mm)	500
Rim Rec	W 12
Rim Alt	W 11 ; 11 ; 12
ECE	E11-106R-002963

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.6	3.8	4.0	4.2	4.4
50	1500	1770	2040	2305	2575	2860	3005	3150	-	-
40	1500	1770	2040	2305	2575	2860	3005	3150	-	-
30	1610	1900	2195	2490	2780	3075	3220	3370	-	-
25	1670	1975	2280	2585	2890	3195	3350	3500	-	-
10 Cyc.	1850	2260	2670	3080	3490	3900	4110	4315	4520	4730
Static	2840	3470	4100	4730	5360	5990	6305	6620	6935	7250

Printed on 20.04.2024 15:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..