

# MULTIMAX MP 522 - Технические спецификации



## Description

MULTIMAX MP 522 — это универсальные шины компании BKT, разработанные для разнообразной агропромышленной техники. Они подходят для телескопических и компактных погрузчиков, а также другой техники, используемой для всех видов землеройных и погрузочных работ. Среди их преимуществ — устойчивость, тяга и исключительно высокое сопротивление проколам. Благодаря специальной резиновой смеси шины MULTIMAX MP 522 обладают невероятной устойчивостью к порезам и разрывам.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Сельское хозяйство: Компактный погрузчик •  
Телескопический погрузчик  
Производство: компактный погрузчик • Телескопический погрузчик

Version	STANDARD
Type	TL
Tyre Size	400/70 R 20 IND (16.0/70 R 20)
LI/SS	149 A8/B

## Dimensions US Standard

Usa code	94033829
Section Width (inch)	15.9
Overall Diameter (inch)	42
Static Loaded Radius (inch)	18.7
Rolling Circumference (inch)	126.9
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E4-106R-002319

## Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	3440	4090	4660	5300	5950	6380	7160	-	-
25	3440	4090	4660	5300	5950	6380	7160	-	-
20	3690	4380	4990	5690	6370	6830	7670	-	-
15	3820	4540	5180	5900	6610	7090	7960	-	-
5 Cyc	4200	5160	6070	6990	7960	8650	9790	10320	10750
Static	6440	7910	9310	10710	12200	13270	15000	15830	16480

Printed on 20.04.2024 11:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..