

MULTIMAX MP 522 - Технические спецификации



Description

MULTIMAX MP 522 — это универсальные шины компании BKT, разработанные для разнообразной агропромышленной техники. Они подходят для телескопических и компактных погрузчиков, а также другой техники, используемой для всех видов землеройных и погрузочных работ. Среди их преимуществ — устойчивость, тяга и исключительно высокое сопротивление проколам. Благодаря специальной резиновой смеси шины MULTIMAX MP 522 обладают невероятной устойчивостью к порезам и разрывам.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Компактный погрузчик •
Телескопический погрузчик
Производство: компактный погрузчик • Телескопический погрузчик

Version	STANDARD
Type	TL
Tyre Size	440/80 R 28 IND
LI/SS	156 A8/B

Dimensions US Standard

Usa code	94052240
Section Width (inch)	17.4
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	168.4
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-002968

Load capacity (lbs)

mph / psi	23	29	32	35	38	41	44	46	49	52
30	5070	6010	6480	6940	7410	7880	8360	8820	-	-
25	5070	6010	6480	6940	7410	7880	8360	8820	-	-
20	5470	6460	6960	7450	7950	8440	8940	9440	-	-
15	5670	6700	7210	7730	8240	8750	9270	9790	-	-
5 Cyc.	6260	7650	8360	9050	9740	10440	11130	11840	12530	13230
Static	9610	11750	12810	13880	14950	16020	17080	18140	19210	20280

Printed on 20.04.2024 5:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..