

MULTIMAX MP 525 - Технические спецификации



Description

MULTIMAX MP 525 — многоцелевая радиальная шина с цельным металлокордом, разработанная для телескопических и компактных погрузчиков, а также грейдеров, используемых в аграрной промышленности. Эта модель выдерживает большие нагрузки на высоких скоростях при эксплуатации как на дорогах с покрытием, так и на бездорожье. Крупный, ненаправленный рисунок протектора обеспечивает исключительную тягу на любых поверхностях, а также обладает отличными самоочищающимися свойствами. Прочные боковины гарантируют выдающуюся поперечную устойчивость при подъеме грузов, что делает эту шину идеальным вариантом для техники, выполняющей сельскохозяйственные и погрузочно-разгрузочные работы. Шина MULTIMAX MP 525 изготовлена из уникального компаунда, стойкого к порезам и проколам. Благодаря этому она отличается долгим сроком службы.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: компактный погрузчик • Грейдер •
Телескопический погрузчик

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 (16.0/70 R 20)
LI/SS	152 J/168 A2

Dimensions US Standard

Usa code	94072873
Overall Width (inch)	15.9
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19
Rolling Circumference (inch)	128.3
Rim Rec	13
Rim Alt	12; 13 SDC
ECE	E11-54R-0020576

Load capacity (lbs)

mph / psi	87
62	7830
5	12350

Printed on 30.04.2024 18:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..