

## MULTIMAX MP 540 - Технические спецификации



### Description

Модель MULTIMAX MP 540 от компании BKT разработана специально для многоцелевых транспортных средств. Благодаря стальному каркасу шины MULTIMAX MP 540 позволяют перевозить тяжелые грузы как по дорогам с покрытием, так и по бездорожью. Кроме того, распределение блоков протектора обеспечивает превосходную устойчивость и долговечность.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Универсальный автомобиль

Производство: Универсальный автомобиль

Version	STANDARD
Type	TL
Tyre Size	405/70 R 24 (16.0/70 R 24)
LI/SS	152 J

## Dimensions US Standard

Usa code	94074600
Overall Width (inch)	15.8
Overall Diameter (inch)	46.2
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	141.2
Rim Rec	13
ECE	E11-54R-0020862

## Load capacity (lbs)

mph / psi	73
62	7830

Printed on 25.04.2024 8:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..