



MULTIMAX MP 540 - Загрузить лист технических данных



Description

Модель MULTIMAX MP 540 от компании BKT разработана специально для многоцелевых транспортных средств. Благодаря стальному каркасу шины MULTIMAX MP 540 позволяют перевозить тяжелые грузы как по дорогам с покрытием, так и по бездорожью. Кроме того, распределение блоков протектора обеспечивает превосходную устойчивость и долговечность.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Универсальный автомобиль

Производство: Универсальный автомобиль

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
315/55 R 16	STANDARD	94068999	120 K / 124 F	W10L	11	12	29.6	13.9	91.5	TL	E11-54R-0019558
335/80 R 18 (12.5 R 18)	STANDARD	94069422	132 K			13.4	38.8	17.6	118.1	TL	E11-54R-0019559
275/80 R 20 (10.5 R 20)	STANDARD	94071357	134 K	W9	9	10.6	37.6	17.4	114.7	TL	E11-54R-0020628
335/80 R 20	STANDARD	94033539	149 K	11	-	13.4	41.1	19.4	128.3	TL	E11-54R-0015909
365/80 R 20 (14.5 R 20)	STANDARD	94069873	152 K	11		14.4	42.8	19.5	130.2	TL	E11-54R-0020145
405/70 R 20 (16.0/70 R 20)	STANDARD	94072903	152 K	13	12; 13 SDC	15.8	42.6	19.3	129.7	TL	
405/70 R 24 (16.0/70 R 24)	STANDARD	94074600	152 J	13		15.8	46.2	20.9	141.2	TL	E11-54R-0020862

Printed on 25.04.2024 10:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..