

MULTIMAX MT 518 - Технические спецификации



Description

Шины MULTIMAX MT 518 разработаны специально для военных грузовых автомобилей. Эти шины с брекером из металлокорда и с блочным рисунком протектора отличаются высоким сопротивлением проколам, а также превосходной устойчивостью. Кроме того, шины MULTIMAX MT 518 выдерживают высокие скорости и имеют долгий срок службы.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Армейский грузовик

Version	STANDARD
Type	TL
Tyre Size	36 X 12.5 R 16.5
LI/SS	129 N

Dimensions International Standard

Section Width (mm)	315
Overall Diameter (mm)	902
Static Loaded Radius (mm)	420
Rolling Circumference (mm)	2758
Rim Rec	9.75
ECE	E11-54R-0017917

Load capacity (Kg)

km/h / bar	4.5
140	1850

Printed on 03.05.2024 1:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..