

## РАС MASTER - Технические спецификации



### Description

РАС MASTER - это диагональные шины для уплотнительной техники. Среди их преимуществ - высокий уровень стабильности и долгий срок службы. За счет использования особой резиновой смеси, шины обладают исключительной термостойкостью.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Производство: уплотнительная техника

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 10.5/80 - 16 |

## Dimensions International Standard

|                                   |                 |
|-----------------------------------|-----------------|
| <b>Ply Rating</b>                 | 14              |
| <b>Section Width (mm)</b>         | 275             |
| <b>Overall Diameter (mm)</b>      | 810             |
| <b>Static Loaded Radius (mm)</b>  | 382             |
| <b>Rolling Circumference (mm)</b> | 2480            |
| <b>Rim Rec</b>                    | 8.0             |
| <b>ECE</b>                        | E11-106R-004647 |

## Load capacity (Kg)

|  | km/h / bar | 6.00 |
|--|------------|------|
|  | 10         | 2775 |
|  | 15         | 2250 |

Printed on 19.04.2024 18:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..