

PL 801 - Технические спецификации



Description

Шины PL 801 разработаны специально для роторных сменных граблей/сеноворошилок, используемых для сеноуборочных работ, а также для вилочных погрузчиков, задействованных в логистических операциях. Они отличаются превосходной устойчивостью и высокой стойкостью к порезам и разрывам. Шины PL 801 также порадуют своим долгим сроком службы.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сенокосилка • Роторные грабли / Сеноворошилка • Вилочный погрузчик
Производство: Вилочный погрузчик

Version	STANDARD
Type	TT
Tyre Size	18 X 7 - 8 (180/70 - 8)

Dimensions US Standard

Usa code	94006953
Ply Rating	14
Section Width (inch)	6.8
Overall Diameter (inch)	18.5
Rim Rec	4.33 R
Rim Alt	5.00 F

Load capacity (lbs)

	mph / psi	131
15 LOAD WHEEL		4155
15 STEER WHEEL		3195
5 OTHER VEHICLES		4155
15 OTHER VEHICLES		3195
STATIC SIDE LOADER		4830

Printed on 17.04.2024 3:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..