

PL 801 - Технические спецификации



Description

Шины PL 801 разработаны специально для роторных сменных граблей/сеноворошилок, используемых для сеноуборочных работ, а также для вилочных погрузчиков, задействованных в логистических операциях. Они отличаются превосходной устойчивостью и высокой стойкостью к порезам и разрывам. Шины PL 801 также порадуют своим долгим сроком службы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сенокосилка • Роторные грабли / Сеноворошилка • Вилочный погрузчик
Производство: Вилочный погрузчик

Version	STANDARD
Type	TT
Tyre Size	21 X 8 - 9 (200/75 - 9)

Dimensions International Standard

Ply Rating	14
Section Width (mm)	200
Overall Diameter (mm)	535
Rim Rec	6.00 E
Rim Alt	7.00 E
ECE	E11-106R-003643

Load capacity (Kg)

	km/h / bar	9.00
25 LOAD WHEEL		2535
25 STEER WHEEL		1950
10 OTHER VEHICLES		2535
25 OTHER VEHICLES		1950
STATIC SIDE LOADER		2945

Printed on 17.04.2024 5:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..