

PORT KING PLUS - Технические спецификации



Description

Шины PORT KING PLUS созданы специально для контейнерных погрузчиков, используемых для интермодальных/логистических операций. Глубокий рисунок протектора с крупными грунтозацепами наряду с особой резиновой смесью обеспечивают более продолжительный срок службы шины. Они также доступны в версии с канавками из специальной резиновой смеси, стойкой к образованию трещин (GCRC).

UM

International Standard

Construction

 BIAS

Machinery

Производство: Контейнерный погрузчик

Version	GCRC
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	40
Overall Width (mm)	528
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	4955
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	22950

Printed on 24.04.2024 20:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..