

PORT KING PLUS - Технические спецификации



Description

Шины PORT KING PLUS созданы специально для контейнерных погрузчиков, используемых для интермодальных/логистических операций. Глубокий рисунок протектора с крупными грунтозацепами наряду с особой резиновой смесью обеспечивают более продолжительный срок службы шины. Они также доступны в версии с канавками из специальной резиновой смеси, стойкой к образованию трещин (GCRC).

UM

US Standard

Construction

 BIAS

Machinery

Производство: Контейнерный погрузчик

Version	GCRC
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94026593
Ply Rating	40
Overall Width (inch)	20.8
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	195.1
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	50625

Printed on 24.04.2024 20:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..