

PORTMAX PM 90 - Технические спецификации



Description

Шины PORTMAX PM 90 были специально разработаны для контейнерных погрузчиков, используемых для погрузочно-разгрузочных работ в промышленности и на металлургических заводах. Эта радиальная шина с цельным металлокордом обладает отличной прочностью и устойчивостью. Уникальная антистатическая резиновая смесь протектора обеспечивает стойкость к нагреву и долгий срок службы. Шины PORTMAX PM 90 гарантируют пониженное сопротивление качению, способствуя экономии топлива.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Контейнерный погрузчик

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 25
LI/SS	207 A5

Dimensions International Standard

Overall Width (mm)	495
Overall Diameter (mm)	1655
Static Loaded Radius (mm)	730
Rolling Circumference (mm)	5024
Rim Rec	13.00/2.5
Star Rating	***

Load capacity (Kg)

km/h / bar	10
25	17500

Printed on 25.04.2024 0:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..