

## PORTMAX PT 93 - Технические спецификации



### Description

PORTMAX PT 93 — это шина для терминальных тягачей, специально разработанная для эксплуатации в непростых условиях грузовых терминалов, таких как порты и логистические центры. Специальная антистатическая резиновая смесь протектора отличается превосходной износостойкостью и сопротивлением нагреву даже при интенсивной эксплуатации. PORTMAX PT 93 гарантирует отличную управляемость, выдающееся сцепление и увеличенный срок службы.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Производство: терминальный тягач • Прицеп

Version	INDUSTRIAL
Type	TL
Tyre Size	280/75 R 22.5
LI/SS	168 A8

## Dimensions US Standard

Usa code	94053902
Overall Width (inch)	11.1
Overall Diameter (inch)	39.3
Rim Rec	8.25
Rim Alt	9.00

## Load capacity (lbs)

mph / psi	145
25	12300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09.02.2025 16:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..